


端子 TERMINAL(4018/3.96)


型号 Type	适用线规 Applicable wires mm ² AWG#	电线外径 O.D of wire ins mm	材料厚度 Thickness mm	材料 Material	数量 Quantity
HX39602-PTA	0.2~0.75 24~18	1.5~3.0	0.3	黄铜	3000PCS/盘
HX39602-PTB	0.2~0.75 24~18	1.5~3.0	0.25	磷铜	4000PCS/盘

HX39602-PT (4018/3.96)


PTB(磷青铜Phos.bronze)




PTA(黄铜Brass)




HX39602-Y (2139/3.96)




HX39602-PB (2139/3.96)



HX39603-NA (5271/3.96)




HX39603-A (5273/3.96)




技术参数 SPECIFICATIONS

- 线数 (Poles) : 2~16
- 适用线规 (Applicable wires) : AWG24#~18#
- 适应基板厚度 (Applicable PC board thickness) : 1.6mm
- 温度范围 (Temperature range) : -25 °C~85 °C
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 5A
- 接触电阻 (Contact resistance) : ≤0.015Ω
- 绝缘电阻 (Insulation resistance) : ≥1000MΩ
- 耐压 (Withstand voltage) : 1500V.Ac/1min
- 材料 (Material) :
 - 孔座 (Housing) : 尼龙 (PA66) UL94V-2(0)
 - 针座 (Wafer) : 尼龙 (PA66) UL94V-2(0)
 - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated) 黄铜 (Brass Tin/plated)


HX39603-WAP (5274/3.96)



HX39603-WAG (5274/3.96)



安装尺寸 MOUNTING MEASUREMENT



孔座 HOUSING(2139/3.96)

线数 Poles	型号 Type	尺寸Dimensions(mm)	
		A	B
2	HX39602-2Y/PB	3.96	8.52
3	HX39602-3Y/PB	7.92	12.48
4	HX39602-4Y/PB	11.88	16.44
5	HX39602-5Y/PB	15.84	20.40
6	HX39602-6Y/PB	19.80	24.36
7	HX39602-7Y/PB	23.76	28.32
8	HX39602-8Y/PB	27.72	32.28
9	HX39602-9Y/PB	31.68	36.24
10	HX39602-10Y/PB	35.64	40.20
11	HX39602-11Y/PB	39.60	44.16
12	HX39602-12Y/PB	43.56	48.12
13	HX39602-13Y/PB	47.52	52.08
14	HX39602-14Y/PB	51.48	56.04
15	HX39602-15Y/PB	55.44	60.00
16	HX39602-16Y/PB	59.40	63.96

针座 WAFER(5273/5274/5271/3.96)

线数 Poles	型号 Type		尺寸Dimensions(mm)		
	直式弯式	横条(180°)	A	B	C
2	HX39603-2A/WA	HX39603-2NA	3.96	7.92	7.77
3	HX39603-3A/WA	HX39603-3NA	7.92	11.88	11.73
4	HX39603-4A/WA	HX39603-4NA	11.88	15.84	15.69
5	HX39603-5A/WA	HX39603-5NA	15.84	19.80	19.65
6	HX39603-6A/WA	HX39603-6NA	19.80	23.76	23.61
7	HX39603-7A/WA	HX39603-7NA	23.76	27.72	27.57
8	HX39603-8A/WA	HX39603-8NA	27.72	31.68	31.53
9	HX39603-9A/WA	HX39603-9NA	31.68	35.64	35.49
10	HX39603-10A/WA	HX39603-10NA	35.64	39.60	39.45
11	HX39603-11A/WA	HX39603-11NA	39.60	43.56	43.41
12	HX39603-12A/WA	HX39603-12NA	43.56	47.52	47.37
13	HX39603-13A/WA	—	47.52	51.48	—
14	HX39603-14A/WA	—	51.48	55.44	—
15	HX39603-15A/WA	—	55.44	59.40	—
16	HX39603-16A/WA	—	59.40	63.36	—